
REVISIONS

ZONE REV. DESCRIPTION DATE APPROVED

INFORMATION IN THIS DRAWING PROVIDED FOR REFERENCE ONLY

6.563±.020 - 2.125 - 2.313 2.125 REF.. .160 -1.40-GROOVE TYP. TYP. 5/16-18 x 5/16" SOC. SET SCREW .090 .50 TYP. TYP. .03 x 45° TYP Ø1 50 Ø1.435 **GROOVE** TYP.



TYPICAL BOTH ENDS

NOTE(s), UNLESS OTHERWISE SPECIFIED.

SCALE 1:1

- (1) UNIVERSAL JOINT IS MARKED W/ "BELDEN" LOGO, PART NUMBER / DRAWING NUMBER, REVISION LEVEL (IF ANY), DATE OF MANUFACTURE (MO/YR), AND BELDEN JOB NUMBER.
- (2) UNIVERSAL JOINT IS LUBRICATED w/ LUBRIPLATE 1200-2, NLGI GRADE 2, AW/EP, LITHIUM GREASE OR EQUIVALENT.
- (3) UNIVERSAL JOINT IS CAPABLE OF OPERATING AT ANY ANGLE UP TO AND INCLUDING 45°, 90° FOR THE DOUBLE UNIVERSAL JOINT.
- (4) UNIVERSAL JOINT HAS STANDARD GROOVES TO ACCEPT INSTALLATION OF PROTECTIVE COVERS (BOOTS). BOOTS AVAILABLE SEPARATELY. REFER TO BELDEN CATALOG, WEBSITE, OR CONTACT BELDEN SALES.
- (5) REFER TO BELDEN CATALOG, WEBSITE, OR CONTACT BELDEN SALES FOR TORQUE CAPACITY.
- (6) THIS DRAWING REPRESENTS A STANDARD BELDEN ITEM.
 CUSTOM UNIVERSAL JOINTS ARE AVAILABLE UPON REQUEST. PLEASE CONTACT BELDEN SALES.

BELDEN PART NUMBER: DUJ-HD1500x750K

DO NOT SCALE DRAWING

DO NOT SCALL DRAWING							
UNLESS OTHERWISE SPECIFIED		MATERIAL		NAME	DATE	Belden Incorporated	
CHAMFER ALL HOLES BREAK ALL SHARP CORNERS	UNLESS OTHERWISE SPECIFIED	ALLOY STEEL	DRAWN	JP	30MAR12	www.beldenuniversal.com	
DE-BURR ALL FEATURES	DIMENSIONS ARE IN INCHES [mm]		CHECKED	RNK	23APR12	TITLE:	
TURNED SURFACES: 63	ANGULAR MACHINED: ±1.0° FRACTIONAL: ±.015"	SEE DETAIL	ENG APPR.		23APR12	1 40054511/	
MILLED SURFACES: 125	TWO PLACE DECIMAL: ±.010" THREE PLACE DECIMAL: ±.005"	DRAWINGS	MFG APPR.			DOUBLE U-JOINT	
PROPRIETARY AND CONFIDENTIAL	FOUR PLACE DECIMAL: ±.0005" CONCENTRICITY: .0025" T.I.R.		Q.A. COMMENTS:				
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BELDEN INCORPORATED. ANY	ALL HOLES TO BE LOCATED ON CENTERLINE (\$\mathbb{Q}\$) WITHIN .005" T.I.R.	NONE				SIZE DWG. NO. REV	
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BELDEN INCORPORATED IS PROHIBITED.	INTERPRET GEOMETRIC TOLERANCES					SCALE: 5:4 WT (Lbs): 2.318 SHEET 1 OF 2	
	2		2			SCALE, 3.4 WI (EDS), 2.316 SHEEL LOF 2	