DESCRIPTION SWING DIAMETER INFORMATION IN THIS DRAWING PROVIDED FOR REFERENCE ONLY SECTION A-A **SCALE 2:1** 2.688±.010 1.344 1.344 .068 TYP \TYP .03 x 45°±5° .120 TYP TYP  $\emptyset.75$ TYP  $\emptyset.685$ GROOVE-TYP BELDEN PART NUMBER: SS-UJ-NB750x00 NOTE(s), UNLESS OTHERWISE SPECIFIED (1) UNIVERSAL JOINT IS MARKED W/ "BELDEN" LOGO, PART NUMBER / DRAWING NUMBER, REVISION LEVEL (IF ANY), DATE OF MANUFACTURE (MO/YR), AND BELDEN JOB NUMBER. DO NOT SCALE DRAWING (2) UNIVERSAL JOINT IS LUBRICATED W/ TRIBOLUBE 12, NLGI GRADE 2, MULTI-PURPOSE SYNTHETIC GREASE. INLESS OTHERWISE SPECIFIE STANDARD TOLERANCES, UNLESS OTHERWISE SPECIFIED Belden Incorporated (3) UNIVERSAL JOINT IS CAPABLE OF OPERATING AT ANY ANGLE UP TO AND INCLUDING 45°, 90° FOR THE DOUBLE UNIVERSAL JOINT. STAINLESS STEEL JP 19MAR1 RAWN www.beldenuniversal.com HECKED (4) UNIVERSAL JOINT HAS STANDARD GROOVES TO ACCEPT INSTALLATION OF PROTECTIVE COVERS (BOOTS) BOOTS AVAILABLE SEPARATELY. REFER TO BELDEN CATALOG, WEBSITE, OR CONTACT BELDEN SALES. ASSEMBLY, NG APP SEE DETAIL NEEDLE BEARING FG APPI (5) REFER TO BELDEN CATALOG, WEBSITE, OR CONTACT BELDEN SALES FOR TORQUE CAPACITY. C APPR. UNIVERSAL JOINT COMMENTS SIZE DWG. NO. (6) THIS DRAWING REPRESENTS A STANDARD BELDEN ITEM. ALL HOLES TO BE LOCATED ON CENTERLINE (\$\mathbb{Q}\) WITHIN .005" T.I.R SS-UJ-NB750x00

NTERPRET GEOMETRIC TOLERANCES I.A.W. ASME Y14.5

SCALE: 3:1 WT (Lbs): 0.276 SHEET 1 OF 2