APPROVED INFORMATION IN THIS DRAWING PROVIDED FOR REFERENCE ONLY - 3.375±.010 · .060 REF. TYP -1.188· TYP. .03 x 45° REF.. .160 TYP. Ø1.08 TYP. SWING DIA. Ø1.00 TYP Ø.501^{+.000} √ Ø.56 X 90° INCL Ø.935 GROOVE-TYP. TYPICAL BOTH ENDS NOTE(s), UNLESS OTHERWISE SPECIFIED. BELDEN PART NUMBER: UJ-NB1000x500 (1) UNIVERSAL JOINT IS MARKED W/ "BELDEN" LOGO, PART NUMBER / DRAWING NUMBER, REVISION LEVEL (IF ANY), DATE OF MANUFACTURE (MO/YR), AND BELDEN JOB NUMBER. (2) UNIVERSAL JOINT IS LUBRICATED w/ TRIBOLUBE 12, NLGI GRADE 2, MULTI-PURPOSE SYNTHETIC GREASE. DO NOT SCALE DRAWING (3) UNIVERSAL JOINT IS CAPABLE OF OPERATING AT ANY ANGLE UP TO AND INCLUDING 45°, 90° FOR THE DOUBLE UNIVERSAL JOINT. UNLESS OTHERWISE SPECIFIEE CHAMFER ALL HOLES BREAK ALL SHARP CORNERS STANDARD TOLERANCES, UNLESS OTHERWISE SPECIFIED Belden Incorporated ALLOY STEEL JP 02JUL13 www.beldenuniversal.com (4) UNIVERSAL JOINT HAS STANDARD GROOVES TO ACCEPT INSTALLATION OF PROTECTIVE COVERS (BOOTS) RNK 03JUL13 BOOTS AVAILABLE SEPARATELY. REFER TO BELDEN CATALOG, WEBSITE, OR CONTACT BELDEN SALÈS ASSEMBLY, TURNED SURFACES: \bigvee^{63} RNK 03JUL13 UNIVERSAL JOINT. (5) REFER TO BELDEN CATALOG, WEBSITE, OR CONTACT BELDEN SALES FOR TORQUE CAPACITY. **NEEDLE BEARING** (6) THIS DRAWING REPRESENTS A STANDARD BELDEN ITEM. DWG. NO. REV CUSTOM UNIVERSAL JOINTS ARE AVAILABLE UPON REQUEST. PLEASE CONTACT BELDEN SALES. ALL HOLES TO BE LOCATED ON CENTERLINE (\$\mathbb{C}\) WITHIN .005* T.I.R

Pade Tot 1

NTERPRET GEOMETRIC TOLERANCE I.A.W. ANSI Y14.5M-1982

UJ-NB1000x500

SCALE: 2:1 WT (Lbs): 0.470 SHEET 1 OF 2